


4" Faircloth Skimmer® Surface Drain Cut Sheet

J. W. Faircloth & Son, Inc.
www.FairclothSkimmer.com



1. Coupling can be removed and hose attached to outlet using the threaded 3" nipple. Typical methods used: a) a metal structure with a steel stub out welded on the side at the bottom with a 3" threaded coupling or reducer(s); b) a concrete structure with a hole or orifice at the bottom - use a steel plate with a hole cut in it and coupling welded to it that will fit over the hole in the concrete and bolted to the structure with sealant; or c) it is possible to grout a 4" pvc pipe in a hole in the concrete to connect the skimmer but this is less secure than other methods.
 2. Dimensions are approximate, not intended as plans for construction.
 3. Barrel (solid, not foam core pipe) should be 1.4 times the depth of water with a minimum length of 8' so the inlet can be pulled to the side for maintenance. If more than 10' long, weight may have to be added to inlet to counter the increased buoyancy.
 4. Orifice/inlet tapers down from 4" maximum inlet to a 3" barrel and hose. Barrel is smaller to reduce buoyancy and tendency to lift inlet but is sufficient for flow through inlet because of slope. The orifice/inlet can be reduced using the plug and cutter provided to control the outflow rate – see #6.
 5. Horizontal intake is 8" pipe between the straps with slots cut in the inlet and aluminum screen door (smaller than shown in illustration) for access to the 4" inlet and orifice inside.
 6. **Capacity:** 20,109 cubic feet per day maximum with 4" inlet and 4" head. Inlet can be reduced by installing a smaller orifice using the plug and cutter provided to adjust flow rate for the particular drawdown time required. Please use the sizing template at www.fairclothskimmer.com.
 7. Ships assembled. User glues inlet extension and barrel, installs vent, cuts orifice in plug and attaches to outlet pipe or structure. Includes float, flexible hose, rope, orifice plug and cutter. Does NOT include 3" Sch 40 SOLID pvc barrel or "arm" SUPPLIED BY USER.
- 4inchCut 5-1-2019