


# 2" Faircloth Skimmer® Cut Sheet

[www.FairclothSkimmer.com](http://www.FairclothSkimmer.com)



1. Skimmer can be attached to a straight 4" sch 40 pipe but the pipe may need to be anchored to the bottom at the connection so it is secure. Coupling can be removed and hose attached to outlet using the threaded 2" fitting.
2. Dimensions are approximate, not intended as plans for construction.
3. Barrel (solid, not foam core pipe) should be 1.4 times the depth of water with a minimum length of 6' so the inlet can be pulled to the side for maintenance. If more than 8' long, weight may have to be added to inlet to counter the increased buoyancy.
4. Orifice/inlet tapers down from 2" maximum inlet to a 1 1/2" barrel and hose. Barrel is smaller to reduce buoyancy and tendency to lift inlet but is sufficient for flow through inlet because of slope. The orifice/inlet can be reduced using the plug and cutter provided to control the outflow rate – see #6.
5. Horizontal intake is 4" pipe between the straps with aluminum screen door for access to the inlet and orifice inside.
6. **Capacity:** 3,283 cubic feet per day maximum with 2" inlet and 2" head. Inlet can be reduced by installing a smaller orifice using the plug and cutter provided to adjust flow rate for the particular drawdown time required. Please use the sizing template available at [www.fairclothskimmer.com](http://www.fairclothskimmer.com).
7. Ships assembled. User glues inlet extension and barrel, installs vent, cuts orifice in plug and attaches to outlet pipe or structure. Includes float, flexible hose with fittings, rope, orifice plug & cutter. Does **NOT** include 1 1/2" Sch 40 SOLID pvc barrel or "arm" SUPPLIED BY USER.